

The V35 Vertigo from StormAudio is a marvel in disguise. This Vertigo's first amplifier has our exclusive and patented StormFocus technology allowing the music to be delivered to its full potential.



Features

StormFocus integrated

StormFocus is an amazing improvement in amplifier design that pushes the performance of music to unprecedented levels of accuracy and spatial resolution. You have to hear it to believe it!

Huge dynamic capacity

Left & right channels have a bank of 20 capacitors ensuring a generous dynamic capacity. This, associated with 4 separate windings for the transformer, ensures an incredibly dynamic fast performance for a modest power rating of only 2 x 70 W into 8 ohms.

Separate amplifier and pre-amp sections

Functioning completely independently, both mono amplifiers and pre-amp, allow your system to deliver its full potential and to evolve.

Vibration influence taken to its height

The transformer is decoupled from its surroundings by the use of special inert material and the whole structure is supported by three vibration absorbing feet. This attention to detail effectively reduces transient vibrations and other migratory acoustic parasites that affect the highly sensitive audio signal.

Exclusive build finish

The robust structure that houses the all-important transformer and analogue circuit is utilizing thick aluminum plates finished to a very high standard. Meticulous attention to detail is an integral part of our design philosophy and "savoir faire".

Specifications

Rated Power :

2 x 70 Watts RMS / 8 ohms

Control :

Volume, Source Selection, On/off button on front panel, StormFocus located to the rear of the product.

Remote Control :

Volume, Source selection, On/off function, Mute

Dimensions (L x H x D) :

440 x 80 x 410 mm
(17.32' x 3.15' x 16.14') □

Weight :

13 kg
(28.7 lbs)

Guarantee :

5yrs

Inputs :

5 Line in RCA (phono connector as option)

1 Main In (RCA)

Output :

1 Selector Out (RCA)

1 Pre-out (RCA)

1 Trigger 12V

Sensitivity / impedance input :

550 mV / 25 kΩ

Signal to noise / ratio :

> 105 dB

Bandwidth/pass band :

3 Hz à 200 kHz (± 1.5 dB)

Total Harmonic distortion :

0,015 % at 1 Watt / 8 Ohms

Power Consumption:

Max : 200 Watts

Standby : < 1 Watt

About StormFocus Technology

StormFocus technology undoubtedly brings signal transmission (to the loudspeaker) to the next evolutionary level, enabling the musical energy to be delivered with a unique accuracy.

Our technology introduces a new analog circuit design with an additional setting "StormFocus". This control allows adjustment of the energy delivered to the loudspeaker ensuring the acoustical signal is cleared of the typical phase distortions usually found in most amplifiers. This enables StormAudio amplifiers to produce a real sense of musical presence.

StormFocus technology establishes an ultimate listening performance bringing the musical event to you.

